



HEALTH & SAFETY DATA SHEET

BS5750 : PART 2 : 1987
QAS No. 2567/350
ISO 9002 - 1987
EN 29002 - 1987
Cert. No. FM1090

GLOY GUM

DATE OF ISSUE **APRIL 1991**

REVISED

REF.

1.0	<u>Product Uses:</u>	Adhesive for paper, card etc.		
2.0	<u>Chemical Composition:</u>	Aqueous adhesive based on polyvinyl alcohol		
3.0	<u>Physical Properties:</u>			
3.1	Form:	Liquid		
3.2	Colour:	Light brown		
4.0	<u>Health Hazards:</u>			
4.1	Inhalation:	None		
4.2	Ingestion:	Not poisonous, but do not swallow. Do not eat or drink whilst using product		
4.3	Skin Contact:	None		
4.4	Eye Contact:	Can cause irritation. Goggles should be worn if splashing likely		
5.0	<u>Emergency Action-First Aid:</u>			
5.1	Inhalation:	N/A		
5.2	Ingestion:	For small amounts, drink water, for large amounts consult doctor.		
5.3	Skin Contact:	Rinse with copious amounts of water. Remove contaminated clothing.		
5.4	Eye Contact:	Rinse immediately with water.		
6.0	<u>Emergency Action</u>			
6.1	Spillage:	Soak up with inert material eg. sand/sawdust, flush away residual traces with water.		
6.2	Fire:	N/A		
6.3	Flood:	N/A		
7.0	<u>Transport Precautions:</u>	No special requirements		
8.0	<u>Storage Precautions:</u>	Store in cool dry location between 5 °C - 30 °C		
9.0	<u>Regulations:</u>			
9.1	Hazard Symbols:	N/A		
9.2	Risk/Safety Phrases:	N/A		
10.0	<u>Physical Data:</u>			
10.1	Boiling Point:	100 °C	10.9	Solubility in Water: Miscible in all proportions
10.2	Freezing Point:	<0 °C	10.10	Ignition Temperature: N/A
10.3	Density:	1.01	10.11	Explosion Limits: N/A
10.4	Vapour Pressure:	23 mbar	10.12	Thermal Decomposition: -
10.5	Viscosity:	25 Poise	10.13	Hazardous
10.6	pH Value:	7		Decomposition Products: None
10.7	Flash Point:	N/A	10.14	Incompatible Substances: None known
10.8	Odour:	Very slight	10.15	Hazardous Reactions: None

INFORMATION FOR DOCTORS

Henkel Home Improvement and Adhesive products are registered with the National Poisons Centre,
New Cross Hospital. 24 Hours Emergency No. 071-635 9191

This information is given in good faith and is based on extensive experience and actual state of art.
It does not represent a guarantee for the properties of the product. For technical or practical advice on this or any other Unibond product, please contact our Technical Services Department on Winsford (0606) 593933